



## Excelmotive CD II 40

Mineral oil based monograde engine oil for use in Detroit Diesel engines.

Product code: M068

### Product Description:

Excelmotive CD II 40 is manufactured from solvent refined mineral base stocks and a specially selected additive pack, which ensures optimum performance for Detroit Diesel engines. The state of the art additives control the formation of sludge and deposits in high temperature areas. Effective anti-wear / anti-scuff agents have also been included to give long service life and to prevent pitting and scuffing in highly stressed components. The product is now formulated to meet the newer API CF-2 specification.

The additive pack in Excelmotive CD II 40 is designed to provide superior protection in stop start delivery vehicles and long haul delivery fleets and is suitable for on and off road vehicles where a sulphated ash limit is required.

### Applications:

Excelmotive CD II 40 is manufactured to meet the specific requirements of Detroit Diesel engines where a sulphated ash limit of less than 1% is required and to achieve the requirements to meet API CF-2.

### Product Specification:

SAE Viscosity Grade	40
API	CF-2

### Typical Test Data:

Specific Gravity @ 15.6°C	0.895
Kinematic Viscosity @ 100°C (cSt)	14.81
Kinematic Viscosity @ 40°C (cSt)	148.03
Viscosity Index	99
Flash Point (°C)	215
Total Base Number (mg KOH/g)	5.07
Sulphated Ash (%w/w)	0.89