



## Optima SS 10W-40

Semi synthetic passenger car engine oil

Product code: M119

### Product Description:

A semi synthetic multigrade engine oil meeting ACEA and API specifications required by a large number of cars and light commercial vehicles.

Optima SS 10W-40 is manufactured from a balanced blend of top quality mineral and synthetic base stocks to produce a high quality engine oil with outstanding properties. Its naturally higher lubricity offers lower internal friction which reduces engine wear and improves fuel economy. It provides excellent stay in grade performance for a wide range of modern engines.

### Benefits:

- Suitable for a wide range of vehicles
- Stay in grade properties
- Excellent high and low temperature stability
- Superior performance over standard mineral based oils

### Applications:

Optima SS 10W-40 is suitable for normally aspirated and turbocharged highly stressed diesel and petrol engines in passenger cars and light commercial vehicles. It is miscible with all synthetic and mineral based engine oils.

### Product Specification:

|      |               |
|------|---------------|
| API  | SL/CF         |
| ACEA | A3/B3, A3/B4  |
| VW   | 502.00/505.00 |
| MB   | 229.1         |

### Typical Test Data:

|                                   |       |
|-----------------------------------|-------|
| Specific Gravity @ 15.6°C         | 0.888 |
| Kinematic Viscosity @ 100°C (cSt) | 13.66 |
| Kinematic Viscosity @ 40°C (cSt)  | 87.53 |
| Viscosity Index                   | 160   |
| Flash Point COC (°C)              | 224   |
| Pour Point (°C)                   | -33   |
| TBN (mg KOH / g)                  | 10.2  |

### Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.