



Taurus Extreme M3 10W-40

Fully synthetic heavy duty diesel engine oil

Product code: M401

Product Description:

Taurus Extreme M3 10W-40 is another contemporary heavy duty diesel engine oil to be added to the Exol range of Ultra High Performance Diesel engine oils.

Based on a fully synthetic blend of severely hydrotreated base stocks, viscosity index improver, pour point depressant and an innovative additive system, Taurus Extreme M3 10W-40 is the perfect choice for a multitude of modern diesel engine requirements.

Benefits:

- **Approved by MTU**
- Tolerant of severe running conditions
- Superior sludge and deposit control
- Excellent low temperature pumpability
- Meets Euro I, II, III, IV & V emission requirements
- Suitable for use with NOx reduction systems

Application:

Taurus Extreme M3 10W-40 is formulated for use where there is a requirement to satisfy the latest low emission requirements in Euro V engines and is designed to satisfy the longer drain intervals demanded by the OEM. Taurus Extreme M3 10W-40 is particularly suitable for MTU engines where Type 3 lubricants are required as well as a wide variety of other heavy-duty diesel engines requiring an Ultra High Performance Diesel lubricant.

This oil can be used in MTU Series 6R183 engines.

Performance Specification:

ACEA	E4, E7
API	CI-4, CF
MTU	Type 3 (fully approved)
Mercedes-Benz	228.5
MAN	M3377, M3277
Volvo	VDS-3

Renault Trucks	RLD-2, RLD, RXD
Mack	EO-N EO-M Plus
Cummins	CES 20077/78
Caterpillar	ECF-1-a
Deutz	DQC IV-10

Typical Test Data:

Specific Gravity @ 15°C	0.861
Kinematic Viscosity @ 100°C (cSt)	13.53
Kinematic Viscosity @ 40°C (cSt)	87.07
Viscosity Index	158
Pour Point (°C)	-42
Flash Point COC (°C)	234
TBN (mg KOH/g)	12.0
Sulphated Ash (% wt)	1.5