



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Taurus 10W



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Taurus 10W

Mineral oil based monograde engine oil

Product code: M049

Product Description:

Taurus 10W engine oil is a superior quality monograde lubricant. The combination of solvent refined base oils and high technology additives is designed to give maximum protection to engines working under moderate to severe conditions. The state of the art additives prevent build up of carbon and lacquer deposits on piston ring grooves and valve stems and dramatically reduce the corrosive effects of the products of combustion.

Benefits:

Excellent high temperature stability
Improved bore polishing protection
Excellent anti wear performance for reduced engine wear
Excellent sludge control

Applications:

Taurus 10W may be used in a variety of turbocharged and naturally aspirated diesel engines where a monograde SAE 10W lubricant is specified. Typical applications are earth movers, general plant equipment, large and small trucks, vans and taxis. This product may also be suitable for use in plant equipment hydraulic systems, transmissions and torque converters. Refer to manufacturer handbook.

Product Specification:

API	CE/SG
Military	Mil-L-46152B Mil-L-2104D
CCMC	D4
MB	227.0, 227.1
Mack	EO-K
MAN	270, 271
Caterpillar	TO-2
Allison	C3



TECHNICAL DATA SHEET

Typical Test Data:

Specific Gravity @ 15.6°C	0.875
Kinematic Viscosity @ 100°C (cSt)	5.65
Kinematic Viscosity @ 40°C (cSt)	34.51
Viscosity Index	102
Flash Point COC (°C)	205
Pour Point (°C)	-31
TBN (mg KOH / g)	9.17

Health and Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.