



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Taurus 40



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Taurus 40

Mineral oil based monograde engine oil

Product code: M050

Product Description:

Taurus 40 engine oil is a superior quality monograde lubricant. The combination of solvent refined base oils and high technology additives is designed to give maximum protection to engines working under moderate to severe conditions. The state of the art additives prevent build up of carbon and lacquer deposits on piston ring grooves and valve stems and dramatically reduce the corrosive effects of the products of combustion.

This product is blended to meet the requirements of the BR 668 specification.

Benefits:

Excellent high temperature stability
Improved bore polishing protection
Excellent anti wear performance for reduced engine wear
Excellent sludge control

Applications:

Taurus 40 may be used in a variety of turbocharged and naturally aspirated diesel engines where a monograde SAE 40 lubricant is specified. Typical applications are earth movers, general plant equipment, large and small trucks, vans and taxis. This product may also be suitable for use in plant equipment hydraulic systems, transmissions and torque converters. Refer to manufacturer handbook.

Product Specification:

API	CE/SG
Military	Mil-L-46152B, Mil-L-2104D
CCMC	D4
MB	227.0, 227.1
Mack	EO-K
MAN	270, 271
Caterpillar	TO-2
Allison	C3



TECHNICAL DATA SHEET

Typical Test Data:

Specific Gravity @ 15.6°C	0.890
Kinematic Viscosity @ 100°C (cSt)	14.8
Kinematic Viscosity @ 40°C (cSt)	141
Viscosity Index	105
Flash Point COC (°C)	224
Pour Point (°C)	-29
TBN (mg KOH / g)	9.20

Health and Safety:

Please refer to the relevant safety data sheet, a copy of which is freely available to all our customers.