



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Excelmould 802



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Excelmould 802

Mineral oil based mould release fluid

Product code: P002

Product Description:

Excelmould 802 is a light viscosity release agent.

Excelmould 802 is manufactured from highly refined solvent base oil and chemical release agents, which react with concrete to form a barrier between the mould and casting.

It is generally required on the form face to facilitate the easy removal of components from moulds without damaging the concrete surface or formwork.

Benefits:

- Pleasant odour for good worker acceptability
- Light viscosity for easy application
- Contains high levels of release agent
- High flash point

Application:

Excelmould 802 is recommended as a release agent for use on mass production concrete sections on wood or steel moulds. It should be applied by swab, brush or spray and should be applied liberally.

Typical Test Data:

Specific Gravity @ 15.6°C	0.876
Kinematic Viscosity @ 40°C (cSt)	20.5
Flash Point COC (°C)	210
Appearance	Straw

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.