



**EXCELLENCE IN LUBRICANTS**

## *TECHNICAL DATA SHEET*

Excelguard 501



**EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

[WWW.EXOL-LUBRICANTS.COM](http://WWW.EXOL-LUBRICANTS.COM)



# Excelguard 501

Solvent deposited, water displacing rust preventative

Product code: R001

## Product Description:

Excelguard 501 is a solvent deposited water displacing corrosion preventative.

Excelguard 501 is a blend of de-watering agents, corrosion inhibitors, hydrocarbon mineral oils, synthetic sulphonates and hydrocarbon solvents. It offers short term protection of ferrous and aluminium alloy components. It leaves a light oily anti-corrosion film when applied. It is ideally suited to inter-process protection after machining.

## Benefits:

Solvent deposited  
Excellent dewatering properties

## Application:

Excelguard 501 is best applied by dipping, spraying or brushing. If a tank is being used the residual water should be drained off periodically. Allow up to 50 minutes drying time. It may affect some rubbers and plastics on long-term exposure.

## Product Specification:

Protection Indoors	3 - 6 months
Protection Outdoors (covered)	2 months
Protection Outdoors	1 month
Film Thickness	2.1 microns
Covering Capacity	60 m <sup>2</sup> /litre

## Typical Test Data:

Specific Gravity @ 15.6°C	0.830
Kinematic Viscosity @ 40°C (cSt)	3.65
Film Type	Thin oily
Odour	Solvent

## Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.