



**EXCELLENCE IN LUBRICANTS**

## *TECHNICAL DATA SHEET*

Red Rubber Grease



**EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

[WWW.EXOL-LUBRICANTS.COM](http://WWW.EXOL-LUBRICANTS.COM)



# Red Rubber Grease

Rubber compatible grease

Product code: Z025

## Product Description:

Red Rubber grease is for use in hydraulic systems, especially braking systems, where compatibility with natural, styrene butadiene (SBR), and other types of rubber seal is desirable. Due to the vegetable oil base fluid, the grease is resistant to hydrocarbon solvents, notably petrol and diesel. A red dye is incorporated for identification purposes.

## Benefits:

- Compatible with most rubber seals
- Solvent resistant
- Based on vegetable oil
- Dyed red

## Typical Test Data:

Worked Penetration (IP 50)	245-280
Colour	Red
Texture	Medium fibred
Dropping Point (ASTM D2265, °C)	260 min
Effect on natural rubber (volume change)	+1% to +6%
Effect on neoprene rubber (volume change)	-10% to +10%
Corrosive action on - (weight change mg/cc)	
-steel	0.2
-aluminium alloy	0.1
-copper	0.5
-cast iron	Nil
High temperature stability @ 120°C	No gumming

## Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.