



TECHNICAL DATA SHEET

C2 C3 5W-30 GM LS

Fully synthetic low SAPS engine oil

Product code: N243

Product Description:

C2 C3 5W-30 GM LS is a new generation fully synthetic multigrade engine oil formulated from premium hydrocracked synthetic base stocks, the very latest detergent-dispersant additive package and shear stable polymers.

The reduced levels of SAPS (sulphated ash, phosphorus and sulphur) in C2 C3 5W-30 GM LS ensures compatibility with after treatment systems, such as particulate filters and catalytic converters, and its frictional characteristics promote a reduction in fuel consumption.

Benefits:

- After treatment system compatible
- Extended drain intervals
- Promotes reduced fuel consumption
- Ensures maximum engine protection
- Excellent high and low temperature stability

Applications:

C2 C3 5W-30 GM LS is recommended for use in a wide variety of passenger cars and vans fitted with petrol and diesel engines. Manufacturers include Chrysler, Citroen, Daewoo, Daihatsu, Honda, Hyundai, Isuzu, Land Rover, Lexus, Mazda, Mercedes Benz, Nissan, Peugeot, Renault, Saab, Subaru, Suzuki, Toyota and Vauxhall.

Product Specification:

ACEA	C2, C3
API	SN
General Motors	dexos2™
Mercedes-Benz	229.52, 229.51, 229.31
PSA	B71 2290



TECHNICAL DATA SHEET

Typical Test Data:

Kinematic Viscosity @ 100°C (cSt)	12.3
Kinematic Viscosity @ 40°C (cSt)	73.1
Viscosity Index	167
Density @ 15°C	0.852
Flash Point, COC (°C)	230
TBN (mg KOH/g)	7.5
Cold Cranking Viscosity @ -30°C (cP)	5650

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.