

TECHNICAL DATA SHEET

Taurus Resilient 10W-40

Fully synthetic heavy-duty diesel engine oil. Product code: M385

Product Description:

Taurus Resilient 10W-40 is a premium quality heavy duty diesel engine oil. It is a synthetic blend of severely hydrotreated base stock, viscosity index improver, pour point depressant and a powerful state of the art performance system that is right at the forefront of modern additive technology.

Benefits:

- Unsurpassed engine protection even under the most arduous operating conditions
- Extended drain intervals
- Greater robustness in the presence of biofuels

Applications:

Taurus Resilient 10W-40 is formulated for use where there is a requirement to satisfy the requirements of Scania and is designed to provide the longer drain intervals demanded by the OEM. Taurus Resilient 10W-40 is particularly suitable for Scania engines where piston cleanliness, oxidation, wear and emissions need to be finely controlled. It should be used where a heavy-duty diesel engine oil meeting the Scania LDF-3 specification is called for.

Product Specification:

ACEA	E4, E7	
ΑΡΙ	CF	
Scania	LDF-3 LDF-2, LDF	
Daimler Truck	DTFR 15B120 (formerly	
	MB 228.5)	
DAF	Extended Drains	
MAN	M3277	
Mack	EO-N	

MTU	Туре 3	
Volvo	VDS-3	
Renault	RXD, RLD-2, RLD, RD-2	
Deutz	DQC III-05	
Cummins	20072	
ZF	TE-ML 04C	

Typical Test Data:

Specific Gravity @ 15°C	0.866
Kinematic Viscosity @ 100°C	13.4 cSt
Kinematic Viscosity @ 40°C	89.6 cSt
Viscosity Index	151
Pour Point	-42°C
Flash Point (COC)	244°C
TBN (mg KOH/g)	15.4
Sulphated Ash (% wt)	1.8