



TECHNICAL DATA SHEET

Taurus FS 5W-40

Heavy duty diesel engine oil

Product code: M488

Product Description:

Taurus FS 5W-40 is a fully synthetic heavy duty diesel engine oil which provides enhanced protection across a wide temperature range. It is formulated from premium synthetic base stocks, a sophisticated heavy duty additive package and shear stable polymer chemistry.

Benefits:

- Enhanced low temperature performance
- Excellent base number retention
- Outstanding deposit control on pistons and valves
- Reduced sludge formation
- Excellent anti-wear properties

Applications:

Taurus FS 5W-40 is an ideal choice for use where a SAE 5W-40 grade is the only acceptable viscosity using combination of superior low temperature fluidity and high temperature stability is desired.

Product Specification:

API	CH-4, CF, SL
ACEA	E2, A3/B3, A3/B4
VW	505.00
MB	229.1
Mack	EO-L
MAN	271
MTU	Type 1
Volvo	VDS

Typical Test Data:

SAE Grade	5W-40
Specific Gravity @ 15°C	0.851
Kinematic Viscosity @ 100°C (cSt)	14.5
Kinematic Viscosity @ 40°C (cSt)	91.0
Viscosity Index	166
Flash Point COC (°C)	225
Pour Point (°C)	-36
TBN (mg KOH/g)	10.3