



Autotrans CVT

Fully synthetic continuously variable transmission fluid

Product code: A042

Product Description:

Autotrans CVT is a high performance, fully synthetic transmission fluid designed to provide optimum performance in a wide range of continuously variable transmission (CVT) equipped passenger vehicles.

The specialised performance additive package incorporated into Autotrans CVT has demonstrated equal, and in many cases better, performance than most OEM supplied fluids in areas such as metal to metal wear protection of belt elements and pulleys.

Benefits:

- Exceptional shear stability
- Low temperature fluidity
- Low foaming
- Excellent oxidation resistance
- Anti-shudder durability
- Excellent wear protection

Typical Test Data:

Appearance	Red fluid
Kinematic Viscosity @ 100°C (cSt)	7.20
Kinematic Viscosity @ 40°C (cSt)	33.7
Viscosity Index	185
Flash Point COC (°C)	200
Pour Point (°C)	-48
Brookfield Viscosity @ -40°C (cP)	9020

Applications:

Autotrans CVT is recommended for a use in a wide range of passenger car vehicles fitted with continuously variable transmissions. In particular, Autotrans CVT can be used where any of the following specifications / OEM fluids is required. **Autotrans CVT should NOT be used in conventional stepped automatic transmissions, DCT (Dual Clutch Transmissions), manual transmissions or Toyota e-CVT (THS, Toyota Hybrid System).**



TECHNICAL DATA SHEET

Product Specification:

Audi / VW	TL 052 180 (G 052 180 A1/A2/A6), TL 052 516 (G 052 516)
BMW	8322 0 136 376, 8322 0 429 154 (EZL799, EZL 799A)
Daihatsu	Ammix CVTF-DC
Dodge / Jeep	NS-2 , Mopar CVT 4, CVTF+4
Ford	WSS-M2C928-A (CFT 23), WSS-M2C933-A (CFT 30), Mercon C (CFT 30)
GM	DEX-CVT, GM CVT
Honda	HMMF, HCF-2
Hyundai / Kia	SP-CVT 1
Mazda	CVTF 3320
Mercedes-Benz	MB 236.20, CVT 28
Mitsubishi	DiaQueen CVTF-J1
Nissan	NS-1, NS-2, NS-3
Subaru	High Torque CVTF, Lineartronic CV-30, CVTF II, K0425Y0710, E-CVTF, i-CVTF
Mini Cooper	EZL 799, EZL 799A, ZF CVT V1
Suzuki	CVTF 3320, CVT Fluid Green 1 (Shell Green 1V)
Renault	ELFMATIC
Toyota / Lexus	TC, WS (Prius eCVT only)

Autotrans CVT is also suitable for use out of warranty where the following low viscosity fluids were specified:

Daihatsu	Ammix CVTF-DFE
GM / Saturn	CVTF I-Green2
Mitsubishi	DiaQueen CVTF-J4
Nissan	NS-3
Suzuki	CVTF Fluid Green 2
Toyota / Lexus	FE