



Autotrans DCT

Fully synthetic dual clutch transmission fluid

Product code: A043

Product Description:

Autotrans DCT is a fully synthetic multi-vehicle transmission fluid specifically designed for use in dual clutch transmissions. It is a blend of a premium dual clutch additive package with top quality synthetic base oils which combine to produce a lubricant with a wide range of optimised characteristics.

This includes outstanding frictional durability for improved gear changes over extended periods and excellent load carrying properties for longer transmission life.

Benefits:

- Superior anti-judder performance
- Outstanding anti-wear properties
- Highly shear stable
- Excellent elastomer compatibility
- High levels of thermal & oxidative stability
- Excellent low temperature fluidity

Typical Test Data:

| Appearance | Amber fluid |
|-----------------------------------|-------------|
| Density @ 15.6°C | 0.845 |
| Kinematic Viscosity @ 100°C (cSt) | 6.96 |
| Brookfield Viscosity @ -40°C (cP) | 12,280 |
| Flash Point COC (°C) | 200 |
| Pour Point (°C) | - 45°C |

Applications:

Autotrans DCT is recommended for service fill applications in the vast majority of dual clutch transmission applications on the road today. In particular, Autotrans DCT can be used in any of the following applications.





| OEM | Specification |
|---------------|----------------------------------------|
| BMW | 83 22 2 148 578 |
| | 83 22 2 148 579 |
| | 83 22 0 440 214 (DCTF-1) |
| | 83 22 2 147 477 |
| | 83 22 2 167 666 (MTF LT-5) |
| Chrysler | 68044345 EA & GA |
| Ferrari | TF DCT-F3 |
| Ford | WSS-M2C936-A |
| | MB 236.21 (001 989 85 03) |
| Mercedes-Benz | MB 236.25 (001 989 86 03) |
| | MB 236.24 |
| Mitsubishi | MZ320065 Dia-Queen SSTF-I |
| | Oil No. 999.917.080.00 |
| Porsche | Oil No. 000.043.207.29 |
| | Oil No. 000.043.207.30 |
| PSA | 9734.S2 |
| Renault | EDC-6 |
| | EDC-7 |
| VAG Group | TL 521 82 / G 052 182 A2, G 052 182 A6 |
| | TL 525 29 / G 052 529 A2, G 052 529 A6 |
| | VW G 055 529 |
| Volvo | 1161838, 1161839 |

In addition, Autotrans DCT can be used for service fill applications where any of the following fluids were originally specified: Castrol BOT 341, Castrol BOT 450, Castrol Transmax Dual, Pentosin FFL 2, Pentosin FFL 3, Pentosin FFL 4, Pentosin FFL 52529, Shell TF DCT -F3.