



Excelguard 501A

Solvent deposited, water displacing rust preventative

Product code: R002

Product Description:

Excelguard 501A is a solvent deposited water displacing corrosion preventative.

Excelguard 501A is a blend of de-watering agents, corrosion inhibitors, hydrocarbon mineral oils, synthetic sulphonates and hydrocarbon solvents. It offers short term protection of ferrous and aluminium alloy components. It leaves a light oily anti corrosion film when applied. It is ideally suited to inter-process protection after machining.

Benefits:

- Solvent deposited
- Excellent dewatering properties

Application:

Excelguard 501A is best applied by dipping, spraying or brushing. If a tank is being used the residual water should be drained off periodically. Allow up to 50 minutes drying time. It may affect some rubbers and plastics on long-term exposure.

Product Specification:

Protection Indoors	3 - 6 months
Protection Outdoors (covered)	2 months
Protection Outdoors	1 month
Film Thickness	2.1 microns
Covering Capacity	60 m ² /litre

Typical Test Data:

Specific Gravity @ 15.6°C	0.831
Kinematic Viscosity @ 40°C (cSt)	2.69
Film Type	Thin oily
Odour	Solvent

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.