



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Biodegradable Chainsaw Oil 220



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Biodegradable Chainsaw Oil 220

Vegetable oil based chainsaw oil

Product code: L237

Product Description:

Biodegradable Chainsaw Oil ISO 220 is a stable, non-toxic product which has excellent lubricity. It is environmentally friendly and will not harm forests or watercourses.

Benefits:

Environmentally friendly
Anti-fling properties
Light colour
Non toxic
Excellent lubricity.
High flash point

Application:

Biodegradable Chainsaw Oil ISO 220 is designed for use on the majority of chainsaws.

Typical Test Data:

Specific Gravity @ 15.6°C	0.917
Kinematic Viscosity @ 40°C (cSt)	220.3
Kinematic Viscosity @ 100°C (cSt)	48.09
Viscosity Index	276
Flash Point COC (°C)	>210
Pour Point (°C)	-25
Copper Corrosion	Nil
Appearance	Pale amber, slightly hazy
Biodegradability (CEC-L-33-T-82)	>98%

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.