



**EXCELLENCE IN LUBRICANTS**

## *TECHNICAL DATA SHEET*

Excelmould CC



**EXOL LUBRICANTS LIMITED**

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

[WWW.EXOL-LUBRICANTS.COM](http://WWW.EXOL-LUBRICANTS.COM)



# Excelmould CC

Low viscosity concrete mould release oil

Product code: P036

## Product Description:

Excelmould CC is a low viscosity mould release oil manufactured from a special low viscosity mineral oil combined with a unique hydrocarbon component and is fortified with chemical release agents, which react with concrete to form a barrier between the mould and casting.

Excelmould CC is required on the form face to facilitate the easy removal of components from moulds without damaging the concrete surface.

## Benefits:

- Pleasant odour provides good worker acceptability
- Low viscosity for easy application
- High flash point

## Application:

Excelmould CC is recommended as a release agent for use on mass production concrete sections on wood or steel moulds. It should be applied by swab, brush or spray and should be applied liberally.

## Typical Test Data:

Specific Gravity @ 15.6°C	0.838
Kinematic Viscosity @ 40°C (cSt)	3.8
Flash Point COC (°C)	84
Appearance	Amber

## Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.