



Ultramax VHVI FG

Food grade hydraulic fluid

Product code: See below

Product Description:

Ultramax VHVI FG range are food grade, non-toxic oil developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired. They are blended using carefully selected approved additives to meet the stringent NSF H1 requirements.

Benefits:

- All ingredients are FDA listed
- High viscosity index
- Low coefficient of friction provides excellent lubrication and reduces wear
- Provides excellent wide temperature stability and ensures extended servicing intervals
- Low foaming reduces residue and scum build-up which extends maintenance intervals

Applications:

Ultramax VHVI FG range is suitable for hydraulic systems designed to operate in applications where an oil of this quality is specified. When using for the first time, check the equipment manufacturer's recommendations and the compatibility with any previously used lubricant. For optimum results, purge the system of the previous oil prior to recharging with Ultramax VHVI FG range.

Product Integrity:

Ultramax VHVI FG range is entirely produced from materials which are Kosher and Halal approved and which are NSF H1 registered and meet the USDA 1998 H1 guidelines for incidental contact with food. All ingredients are FDA listed.

Typical Test Data:

	H219	H220	H221
Appearance	Clear Colourless		
ISO VG Grade	32	46	68
Operating Temperature Range	-10°C to +110°C		
Base Oil	Blend of highly refined mineral oils		

Free From Statement:

Ultramax VHVI range does not contain genetically modified ingredients and does not contain any nut oil or derivatives. For a full allergen statement please contact your local representative or our technical department.