



EXCELLENCE IN LUBRICANTS

AUTOMOTIVE & COMMERCIAL GEAR & TRANSMISSION

FLUIDS & LUBRICANTS





LUBRICANTS FOR ALL SECTORS

Contact your Area Sales Manager if you require one of the following brochures from our Lubricants and Fluids Range, alternatively visit **www.exol-lubricants.com/downloads** for an electronic copy.



STATEMENT OF QUALITY

Exol products are supported by O.E.M. approvals, acknowledgments and registrations and a quality guarantee of being of "parts of matching quality" under European Block Exemption Regulations.

These lubricants can be used for vehicle servicing without invalidating the vehicle or replacement parts warranty, providing the application is as given in the Exol Technical Data Sheet.



* Providing the lubricant specification required by the vehicle manufacturer is detailed on the product label or Technical Data Sheet.



AUTOMOTIVE & COMMERCIAL GEAR & TRANSMISSION

Exol's comprehensive range of automotive and commercial gear and transmission lubricants combine a high level of protection with long, trouble free service life. The range includes premium grade fully synthetic, robust semi synthetic and mineral oil based grades for manual and automatic transmissions.

Exol Lubricants is proud to produce and supply the highest quality products that have been approved by Original Equipment Manufacturers (OEMs), for full details please visit Exol's website and select Product Approvals.

Find the right oil for your vehicle with Exol's free online Which Oil look-up, visit www.exol-lubricants.com

Technical Data and Safety Data Sheets are available to view and download through Exol's website product pages.



CONTENTS

FULLY & SEMI SYNTHETIC GEAR OILS
MINERAL GEAR OILS
AUTOMATIC TRANSMISSION FLUIDS
FIND THE PERFECT OIL

4	
5	- 6
8	
1	1

FULLY & SEMI SYNTHETIC GEAR OILS



ATHENA EPZ FS 75W-80 FULLY SYNTHETIC Gear Oil

API GL-4, ZF TE-ML 01L, 02L, 08, 16K, 02A, 02B, 02D, 02E, MAN 341 TYPE Z-4, Z-3, Z-2, Z-1, 341 TYPE E-3, E-2, E-1, 341 ML, 341 N, VOLVO 97305, 97307, MB 235.4, EATON EUROPE 300,000 KM OR 3 YEARS, MILITARY MIL-L-2105

G157D117	20L
G157D00	25L
G157B01	205L
G157I00	1000L IBC
G157T50	BULK



ATHENA SUPER SYNGEAR 75W-90 FULLY SYNTHETIC

Gear Oil

API GL-4, GL-5, MT-1, NATO 0-226, MAN 341 E3 & Z2, 342 M3, MB 235.8, MACK GO-J PLUS, SAE J2360 (PRI GL 0328), SCANIA STO 2:0 A FS, STO 1:0, ARVIN MERITOR 0-76-N, MILITARY MIL-PRF-2105E, VOLVO 97312, DETROIT FLUIDS DF5 93/219.01, ZF TE-ML 028, 058, 07A, 08, 12B, 12L, 12N, 13, 16F, 17B, 19C, 21A

G123D117	20L
G123D00	25L
G123B01	205L
G123I00	1000L IBC
G123T50	BULK



ATHENA PROGEAR MBFS 75W-90 FULLY SYNTHETIC Gear Oil

API GL-4,

MB 235.11

 G166D117
 20L

 G166D00
 25L

 G166B01
 205L

 G166B00
 1000L IBC

 G166T50
 BULK



ATHENA PROGEAR SS 75W-90 SEMI SYNTHETIC Gear Oil

API GL-4, GL-5

G160S515	15 x 1L
G160S715	4 x 5L
G160D117	20L
G160D00	25L
G160B01	205L
G160I00	1000L IBC
G160T50	BULK



ATHENA MULTIGEAR 75W FULLY SYNTHETIC Gear Oil

API GL-4

MULTIPLE MTF APPLICATIONS SEE THE TECHNICAL DATA SHEET FOR FULL LIST OF APPLICATIONS

G167D117	20L
G167D00	25L
G167B01	205L
G167I00	1000L IBC
G167T50	BULK



ATHENA PROGEAR FS 75W-90 FULLY SYNTHETIC Gear Oil

API GL-4, GL-5 COMPREHENSIVE MTF APPLICATIONS SEE THE TECHNICAL DATA SHEET FOR FULL LIST OF APPLICATIONS

G159S515	15 x 1L
G159S715	4 x 5L
G159D117	20L
G159D00	25L
G159B01	205L
G159I00	1000L IBC
G159T50	BULK



ATHENA MULTIGEAR 75W-80 PREMIUM MANUAL

Transmission Fluid

API GL-4, GL-5 MULTIPLE MTF APPLICATIONS SEE THE TECHNICAL DATA SHEET FOR FULL LIST OF APPLICATIONS

G139S535	15 x 1L
G1395704	4 x 5L
G139D117	20L
G139D00	25L
G139B01	205L
G139I00	1000L IBC
G139T50	BULK

MINERAL GEAR OILS



G009D117

G009D00

G009B01

G009100

G009T50

API GL-4, GL-5, MT-1, MILITARY MIL-PRF-2105E, SAE J2360, MACK GO-J, SCANIA STO 1:0, ZF TE-ML 05A, 07A, 08, 12E, 12M, 16B, 16C, 16D, 17B, 21A

Gear Oil

Gear Oil

G008D00

G008B01

G008100

G008T50

API GL-4

G131D117	20L
G131D00	25L
G131B01	205L
G131I00	1000L IBC
G131T50	BULK

API GL-4, GL-5, MT-1, SCANIA STO 1:0, ZF TE-ML 05A, 07A, 08, 12E, 12M, 16B, 16C, 16D, 17B & 21A, MACK GO-J, MILITARY MIL-PRF-2105E, SAE J.2360

G128D117	20L
G128D00	25L
G128B01	205L
G128I00	1000L IBC
G128T50	BULK

G010D117

G010D00

G010B01

G010100

G010T50

201

25L

205L

BULK

1000L IBC

20L

25L

205L

BULK

1000L IBC

MINERAL GEAR DILS

ATHENA P EP 140	ROGEAR	ATHENA F HD 80W	PROGEAR	ATHENA P HD 90	ROGEAR	ATHENA P HD 140	ROGEAR
MINERAL Gear Oil		MINERAL Gear Oil		MINERAL Gear Oil		MINERAL Gear Oil	
API GL-4		API GL-4, GL-5		API GL-4, GL-5		API GL-4, GL-5	
G013D117	20L	G015D117	20L	G016D117	20L	G036D117	20L
G013D00 G013B01	25L 205L	G015D00 G015B01	25L 205L	G016D00 G016B01	25L 205L	G036D00 G036B01	25L 205L
G013I00	1000L IBC	G015001	1000L IBC	G016I00	1000L IBC	G036100	1000L IBC
G013T50	BULK	G015T50	BULK	G016T50	BULK	G036T50	BULK
ATHENA S	AE 90	ATHENAS	5AE 140	ATHENA P LS 90	ROGEAR	ATHENA P LS 80W-90	
MINERAL Gear Oil		Gear Oil		MINERAL LIN Gear Oil	AITED SLIP	MINERAL LIN Gear Oil	
				MINERAL LIN	AITED SLIP	MINERAL LIN	
Gear Oil API GL-1 G021D117	20L	Gear Oil API GL-1 G022D117	20L	MINERAL LIN Gear Oil API GL-5 LS G018D117	20L	MINERAL LIN Gear Oil API GL-5 LS G104S535 G104S704 G104D117	MITED SLIP 15 x 1L 4 x 5L 20L
Gear Oil API GL-1 G021D117 G021D00	20L 25L	Gear Oil API GL-1 G022D117 G022D00	25L	MINERAL LIN Gear Oil API GL-5 LS G018D117 G018D00	20L 25L	MINERAL LIN Gear Oil API GL-5 LS G104S535 G104S704 G104D117 G104D00	MITED SLIP 15 x 1L 4 x 5L 20L 25L
Gear Oil API GL-1 G021D117	20L	Gear Oil API GL-1 G022D117		MINERAL LIN Gear Oil API GL-5 LS G018D117	20L	MINERAL LIN Gear Oil API GL-5 LS G104S535 G104S704 G104D117	MITED SLIP 15 x 1L 4 x 5L 20L

ASK THE EXPERTS

Contact Exol for any issues or technical help. No matter what the question, our team are here to help. Use the following communication lines:



< hello@exol-lubricants.com



www.exol-lubricants.com

FLUID CHECK

Providing fluid analysis & diagnostic services for:

Power Generation & Distribution, Road & Rail Transport, Construction, Mining, Industrial and Marine

What Is Fluid Check?

Fluid Check is Exol Lubricants' market-leading fluid analysis programme for condition monitoring of all types of fluid-lubricated systems and vehicles.

Your equipment represents a significant investment and it's critical that it remains operational at all times. Failure of your equipment can result in loss of production, and associated costs running into thousands of pounds per hour. Imagine if your business was suddenly unable to provide a core service or product. This potential damage to reputation and future business needs to be avoided wherever possible.

Fluid Check helps reduce unplanned downtime, extends oil drains and detects potential failures before they happen.

AUTOMATIC TRANSMISSION FLUIDS



AUTOTRANS ELC FULLY SYNTHETIC

Automatic Transmission Fluid

GM DEXRON® (IIH, FORD MERCON® V, JASO 1-A, ALLISON C-4, TES-295, CATERPILLAR TO-2, MAN 339 TYPE V-1, 339 TYPE Z-2, 339 TYPE Z-3. SEE THE TECHNICAL DATA SHEET FOR THE FULL LIST OF APPLICATIONS.

A045S535	15 x 1L
A045S704	4 x 5L
A045D117	20L
A045D00	25L
A045B01	205L
A045100	1000L IBC
A045T50	BULK



AUTOTRANS MVA FULLY SYNTHETIC

Automatic Transmission Fluid

GM DEXRON® IIIH, FORD MERCON®, MERCON® V, JASO 1A, MB 236.9, ALLISON C4, TES-295, MAN 339 TYPE V-1, TYPE Z-1, Z-2. SEE THE TECHNICAL DATA SHEET FOR THE FULL LIST OF APPLICATIONS.

A036S572	15 x 1L
A036S704	4 x 5L
A036D117	20L
A036D00	25L
A036B01	205L
A036100	1000L IBC
A036T50	BULK



AUTOTRANS DCT FULLY SYNTHETIC

Dual Clutch Transmission Fluid

SUITABLE FOR THE MAJORITY OF WET-CLUTCH DUAL CLUTCH TRANSMISSIONS. SEE THE TECHNICAL DATA SHEET FOR FULL LIST OF APPLICATIONS.

A043S535	15 x 1L
A043S704	4 x 5L
A043D117	20L
A043D00	25L
A043B01	205L
A043100	1000L IBC
A043T50	BULK

(exol)

AUTOTRANS D III

SEMI SYNTHETIC

Transmission Fluid

GM DEXRON® IIIH, DEXRON® IIIG, DEXRON® IID, TASA,

FORD MERCON®, MAN 339F, 339 V1 & Z1, 339 V2 & Z2, VOITH H55.6335. SEE THE TECHNICAL DATA SHEET FOR THE FULL LIST OF APPLICATIONS

Automatic

A020S572

A020S772

A020D117

A020D00

A020B01

A020100

A020T50



AUTOTRANS CVT FULLY SYNTHETIC

Continuously Variable Transmission Fluid

SUITABLE FOR THE MAJORITY OF CONTINUOUSLY VARIABLE TRANSMISSIONS (CVT). SEE THE TECHNICAL DATA SHEET FOR FULL LIST OF APPLICATIONS.

15 x 1L
4 x 5L
20L
25L
205L
1000L IBC
BULK



AUTOTRANS UNIVERSAL D II MINERAL Automatic Transmission Fluid

GM DEXRON® IID, FORD MERCON®, M20 M2C-138CJ, ALLISON CATERPILLAR TO-2, M SEE THE TECHNICAL THE FULL LIST OF AP	C-4, IB 236.1, 236.7. DATA SHEET FOR
A009S516	15 x 1L

A009S716	4 x 5L
A009D117	20L
A009D00	25L
A009B01	205L
A009100	1000L IBC
A009T50	BULK



AUTOTRANS D VI FULLY SYNTHETIC

Automatic Transmission Fluid

GM DEXRON® VI, DEXRON® IIH, DEXRON® IIIG, DEXRON® IID, TASA, JASO 1A, ALLISON C-4, CATERPILLAR TO-2, MB 236.5, VOITH H55.6335, SEE THE TECHNICAL DATA SHEET FOR THE FULL LIST OF APPLICATIONS.

A041S572	15 x 1L
A041S772	4 x 5L
A041D117	20L
A041D00	25L
A041B01	205L
A041I00	1000L IBC
A041T50	BULK



AUTOTRANS G MINERAL Transmission Fluid

FORD M2C33G, M2C33F

	15 x 1L
	4 x 5L
A002D117	20L
A002D00	25L
A002B01	205L
A002100	1000L IBC
A002T50	BULK

15 x 1L

4 x 5L

20L

25L

205L

BULK

1000L IBC



BULK DELIVERY

Exol's fleet of vehicles comprises a mix of dual-purpose vehicles and large tanker trucks to enable us to deliver bulk orders ranging from 500 litres to 32,000 litres on one vehicle.

Clearance Requirements

Rigid Truck dimensions

Length: 36',

Width: 8'6" - requires a minimum of 12' clearance Height: 12'6"

Tanker Truck dimensions

Length: 68',

Width: 8'6" - requires a minimum of 12' clearance Height: 12'6"

Access

Do you have access for your bulk oil delivery service? Please use our handy guides to determine if our vehicle can gain full access to your site and oil storage tanks.

- 1. Can the vehicle gain safe access?
- 2. Range: can we gain access to within 50ft of the storagefacility (tanks)?

Checks & Supervision

Will the tank take the ordered volume? It is essential that a site supervisor is present at all times during the delivery of the oil to ensure that all procedures are met and the oil is delivered safely to tank.

For further information please contact us: Email: Info@exol-lubricants.com | Tel: +44 (0) 121 568 6800

TECHNOLOGY THAT WORKS FOR YOU

All Exol products are supported by our experienced technical department and team of area sales managers. Our technical support is second to none.

For further information please contact us: Email: info@exol-lubricants.com Tel: +44 (0) 121 568 6800

Exol's technical department draws on over 60 years of oil industry experience and expertise, and is here to help you match the right product to the right application. They are also on hand where you have problems, or special requirements.

We take great pride in ensuring that our products are truly worthy of our motto, "Excellence in Lubricants".

Exol's market-leading technical support and partnership program is supported by our comprehensive laboratories at both Wednesbury and Rotherham sites.

Technical Support Initiatives:

- Lubricant advice by phone, email and VRM Look Up
- Recommendation on the correct use of our products
- Lubrication problem solving
- Product information
- Safety and technical datasheets
- Sample analysis on all lubricants through Fluid Check program
- On-site technical support

HOW TO FIND THE PERFECT OIL

To ensure you are picking the correct oil for your vehicle, Exol's Oil Check couldn't be easier: **www.exol-lubricants.com/oil-check**



Simply enter the vehicle's details and we'll do the rest. We can then provide you with an overview of the optimum lubricants for your vehicle.



EXOL LUBRICANTS LIMITED All Saints Road, Wednesbury, West Midlands, WS10 9LL, United Kingdom T: + (0) 121 5686800 F: + (0) 121 5686720

www.exol-lubricants.com





