



EXCELLENCE IN LUBRICANTS

AUTOMOTIVE

FLUIDS & LUBRICANTS



LUBRICANTS FOR ALL SECTORS

Contact your Area Sales Manager if you require one of the following brochures from our Lubricants and Fluids Range, alternatively visit www.exol-lubricants.com/downloads for an electronic copy.



STATEMENT OF QUALITY

Exol products are supported by O.E.M. approvals, acknowledgments and registrations and a quality guarantee of being of “parts of matching quality” under European Block Exemption Regulations.

These lubricants can be used for vehicle servicing without invalidating the vehicle or replacement parts warranty, providing the application is as given in the Exol Technical Data Sheet.

* Providing the lubricant specification required by the vehicle manufacturer is detailed on the product label or Technical Data Sheet.



AUTOMOTIVE

Exol's comprehensive range of automotive lubricants combine a high level of protection to engines and transmissions with long, trouble free service life.

The range includes premium grade low SAPS engines oils, robust semi synthetic and mineral oil based grades and manual and automatic transmission fluids.

Exol Lubricants is proud to produce and supply the highest quality products that have been approved by Original Equipment Manufacturers (OEMs), for full details please visit Exol's website and select Product Approvals.

Find the right oil for your vehicle with Exol's free online Which Oil look-up, visit www.exol-lubricants.com

Technical Data and COSSH Sheets are available to view and download through Exol's website product pages.



CONTENTS

LOW SAPS FULLY SYNTHETIC ENGINE OILS	4 - 5
FULLY & SEMI SYNTHETIC ENGINE OILS	6 - 7
MINERAL ENGINE OILS	8 - 10
4T & 2T ENGINE OILS	11
ANCILLARY PRODUCTS	12
ANTIFREEZE PRODUCTS	13
GREASES	14
FIND THE PERFECT OIL	15



C1 LSZ 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C1, C2,
Ford WSS-M2C934-B,
Jaguar Land Rover
STJLR.03.5005

M413S540	15 x 1L
M413S768	4 x 5L
M413D117	20L
M413D00	25L
M413B01	205L



C2 LSP 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C2, API SN/CF, PSA
B71 2290, RENAULT
RN0700, FIAT 9.55535-S1

M397S535	15 x 1L
M397S766	4 x 5L
M397D117	20L
M397D00	25L
M397B01	205L



C2 C3 LSGM 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C2, C3, API SN, GM
DEXOS2™ (LICENCE NO.
D20312HE169),
MB-APPROVAL 229.52,
229.51, 229.31,
PSA B71 2290

M490S535	15 x 1L
M490S704	4 x 5L
M490D117	20L
M490D00	25L
M490B01	205L



C3 LSV 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C3, VW 504.00/507.00,
BMW LONGLIFE-04,
MB 229.51, PORSCHE C30
(APPROVED UNDER VW
STANDARD 504 00 AND
VW STANDARD 507 00)

M373S531	15 x 1L
M373S731	4 x 5L
M373D117	20L
M373D00	25L
M373B01	205L



C3 LS 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C3, API SN, VW
504.00/507.00, BMW
LONGLIFE-04, MB 229.51,
PORSCHE C30

M404S506	15 x 1L
M404S754	4 x 5L
M404D117	20L
M404D00	25L
M404B01	205L



C3 LSM 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C3, API SM/CF,
BMW LONGLIFE-04,
MB 229.31

M377S532	15 x 1L
M377S732	4 x 5L
M377D117	20L
M377D00	25L
M377B01	205L



C3 LSG 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C3, API SN/CF, GM DEXOS2™,
MB 229.52, 229.51, 229.31, 226.5,
BMW LONGLIFE-04,
VW 502.00/505.01,
RENAULT RN0700, RN0710

M409S540	15 x 1L
M409S756	4 x 5L
M409D117	20L
M409D00	25L
M409B01	205L



C3 LSX 5W-40 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C3, API SN/CF, MB 229.51,
BMW LONGLIFE-04, VW 502.00/505.01,
GM DEXOS2™, APPROVED TO FORD
SPECIFICATION WSS-M2C917-A,
RENAULT RN0700/RN0710,
PORSCHE A40, FIAT 9.55535-S2

M412S572	15 x 1L
M412S755	4 x 5L
M412D117	20L
M412D00	25L
M412B01	205L



C4 LSR 5W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C4,
RENAULT RN0720,
MB 226.51

M414S535	15 x 1L
M414S767	4 x 5L
M414D117	20L
M414D00	25L
M414B01	205L



LSVW 0W-20 FULLY SYNTHETIC Low SAPS Engine Oil

VW 508.00 / 509.00 (TL 52577),
PORSCHE C20

M506S535	15 x 1L
M506S704	4 x 5L
M506D117	20L
M506D00	25L
M506B01	205L



C5 VC 0W-20 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C5, API SN,
VOLVO VCC RBS0-2AE

M472S572	15 x 1L
M472S704	4 x 5L
M472D117	20L
M472D00	25L
M472B01	205L



C2 LSH 0W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C2, API SN/CF

M421S572	15 x 1L
M421S704	4 x 5L
M421D117	20L
M421D00	25L
M421B01	205L



C2 LSF 0W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C2, APPROVED TO
FORD SPECIFICATION
WSS-M2C950-A

M462S535	15 x 1L
M462S704	4 x 5L
M462D117	20L
M462D00	25L
M462B01	205L



C2 LSC 0W-30 FULLY SYNTHETIC Low SAPS Engine Oil

ACEA C2, PSA B71 2312

M471S535	15 x 1L
M471S704	4 x 5L
M471D117	20L
M471D00	25L
M471B01	205L

APPROVALS



Exol carry a wide range of O.E.M. approvals, acknowledgements, and registrations from the world's top vehicle and equipment manufacturers, including the following. For more information, please contact the technical department.

CAT

CUMMINS

FORD

GE JENBACHER

GENERAL MOTORS

MACK

MAN

MERCEDES-BENZ

MTU

MWM

RENAULT

SCANIA

VOITH

VW

VOLVO

ZF



FS 0W-20 FULLY SYNTHETIC Engine Oil

API SN, SN-RC, ILSAC GF-5

M455S535	15 x 1L
M455S704	4 x 5L
M455D117	20L
M455D00	25L
M455B01	205L



FS 0W-30 FULLY SYNTHETIC Engine Oil

ACEA A5/B5, A1/B1, API SL/CF, VW 503.00, BMW LONGLIFE-01 FE

M344S535	15 x 1L
M344S704	4 x 5L
M344D117	20L
M344D00	25L
M344B01	205L



FS 0W-40 FULLY SYNTHETIC Engine Oil

ACEA A3/B3, A3/B4, API SN/CF, VW 502.00/505.00, MB 229.5, BMW LONGLIFE-01, RENAULT RN0700/0710, PORSCHE A40

	15 x 1L
	4 x 5L
M369D117	20L
M369D00	25L
M369B01	205L



FE 5W-20 FULLY SYNTHETIC Engine Oil

ACEA C5, API SN/CF, ILSAC GF-5, APPROVED TO FORD SPECIFICATION WSS-M2C948-B, WSS-M2C925-B, JAGUAR LAND ROVER STJLR.03.5004, CHRYSLER MS 6395

M439S535	15 x 1L
M439S764	4 x 5L
M439D117	20L
M439D00	25L
M439B01	205L



FD 5W-30 FULLY SYNTHETIC Engine Oil

ACEA A5/B5, A1/B1, API SL/CF, APPROVED TO FORD SPECIFICATIONS WSS-M2C913-D, WSS-M2C913-C, JAGUAR LAND ROVER STJLR.03.5003, RENAULT RN0700

M396S546	15 x 1L
M396S746	4 x 5L
M396D117	20L
M396D00	25L
M396B01	205L



DX1 5W-30 FULLY SYNTHETIC Engine Oil

API SN PLUS, SN, GM DEXOS1™ GEN 2, ILSAC GF-5

M497S535	15 x 1L
M497S704	4 x 5L
M497D117	20L
M497D00	25L
M497B01	205L



LONGLIFE 5W-30 FULLY SYNTHETIC Engine Oil

ACEA A3/B4, API SM/CF, VW 502.00/505.00, MB 229.5, GM LL-A-025, LL-B-025, BMW LONGLIFE-01, LONGLIFE-98

M380S544	15 x 1L
M380S744	4 x 5L
M380D117	20L
M380D00	25L
M380B01	205L



FS 5W-30 FULLY SYNTHETIC Engine Oil

ACEA A5/B5, A1/B1, API SL/CF, FORD WSS-M2C913-B, BMW LONGLIFE-01 FE, ILSAC GF-2

M400S535	15 x 1L
	4 x 5L
M400D117	20L
M400D00	25L
M400B01	205L



FS 5W-40 FULLY SYNTHETIC Engine Oil

ACEA A3/B3, A3/B4,
API SL/CF, VW 502.00/505.00,
MB 229.3, GM LL-B-025,
BMW LONGLIFE-98, RENAULT
RN0700/RN0710, PORSCHE A40

M091S501	15 x 1L
M091S701	4 x 5L
M091D117	20L
M091D00	25L
M091B01	205L



PD 5W-40 FULLY SYNTHETIC Engine Oil

API SN/CF, ACEA A3/B3, A3/B4,
VW 502.00, 505.00, 501.01,
MB 229.5, 229.3, GM LL-B-025,
BMW LL-01, RENAULT RN0700,
RN0710, PORSCHE A40, PSA B71 2296
(See Technical Data Sheet for further information)

	15 x 1L
	4 x 5L
M411D117	20L
M411D00	25L
M411B01	205L



SPORT 10W-60 FULLY SYNTHETIC High Performance Engine Oil

ACEA A3/B3, A3/B4, API SN/CF

M482S535	15 x 1L
M482S704	4 x 5L
M482D117	20L
M482D00	25L
M482B01	205L



SS 10W-40 SEMI SYNTHETIC Engine Oil

ACEA A3/B3, A3/B4,
API SL/CF, MB 229.1
VW 502.00/505.00,

M119S502	15 x 1L
M119S702	4 x 5L
M119D117	20L
M119D00	25L
M119B01	205L



SS 5W-30 SEMI SYNTHETIC Engine Oil

ACEA A1/B1, API SL/CF,
FORD WSS-M2C913-B &-A,
BMW LONGLIFE-01 FE,
ILSAC GF-2

M113S503	15 x 1L
M113S703	4 x 5L
M113D117	20L
M113D00	25L
M113B01	205L

FLUID CHECK



Providing fluid analysis & diagnostic services for:

Power Generation & Distribution, Road & Rail Transport,
Construction, Mining, Industrial and Marine

What Is Fluid Check?

Fluid Check analysis is Exol Lubricants' market leading complete fluid analysis programme for monitoring all types of fluid lubricated and insulating oil systems.

In all cases your machinery represents a significant investment by your company and it is so critical it remains operational at all times. Failure of your machinery can result in loss of operation, with associated costs running at times into thousands of pounds an hour.

Imagine if your business was suddenly unable to provide its services or product, consider the damage it could do to your business and your customers' confidence in you to deliver on time or even at all...it must not happen - if it can be avoided!

Our aim is to help you succeed in making the most of your vehicles and machinery through reducing unplanned downtime, extending oil drains and detecting potential future failure...before they happen!



OPTIGUARD 10W-30 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL/CH-4, CF, VW 505.00, MB 229.1, MACK EO-L, MAN 271, MTU TYPE 1, VOLVO VDS

	15 x 1L
M111S706	4 x 5L
M111D117	20L
M111D00	25L
M111B01	205L



OPTIGUARD 10W-40 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL/CH-4, CF, VW 505.00, MB 229.1, MACK EO-L, MAN 271, MTU TYPE 1, VOLVO VDS

	15 x 1L
M102S507	4 x 5L
M102D117	20L
M102D00	25L
M102B01	205L



OPTIGUARD 15W-40 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL/CH-4, CF, VW 505.00, MB 228.1, 229.1, MACK EO-L, MAN 271, MTU TYPE 1, VOLVO VDS

	15 x 1L
M099S505	4 x 5L
M099S705	20L
M099D117	25L
M099D00	205L
M099B01	



OPTIGUARD 20W-50 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL/CH-4, CF, VW 505.00, MB 228.1, 229.1, MACK EO-L, MAN 271, MTU TYPE 1, VOLVO VDS

	15 x 1L
M166S570	4 x 5L
M166S770	20L
M166D117	25L
M166D00	205L
M166B01	



OPTIGUARD 10W MINERAL Engine Oil

API SL, CH-4, CF, MB 228.0

	15 x 1L
	4 x 5L
M306D117	20L
M306D00	25L
M306B01	205L



OPTIGUARD 20W MINERAL Engine Oil

API SL, CH-4, CF, MB 228.0

	15 x 1L
	4 x 5L
M394D117	20L
M394D00	25L
M394B01	205L



OPTIGUARD 30 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL, CH-4, CF, MB 228.0, MTU TYPE 1

	15 x 1L
	4 x 5L
M305D117	20L
M305D00	25L
M305B01	205L



OPTIGUARD 40 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2, API SL, CH-4, CF, MB 228.0, MTU TYPE 1

	15 x 1L
	4 x 5L
M304D117	20L
M304D00	25L
M304B01	205L



OPTIGUARD 50 MINERAL Engine Oil

ACEA A3/B3, A3/B4, E2,
API SL, CH-4, CF,
MB 228.0, MTU TYPE 1

	15 x 1L
	4 x 5L
M303D117	20L
M303D00	25L
M303B01	205L



CLASSIC 15W-40 MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M004D117	20L
M004D00	25L
M004B01	205L



CLASSIC 20W-50 MINERAL Engine Oil

API SE/CC

M005S504	15 x 1L
M005S704	4 x 5L
M005D117	20L
M005D00	25L
M005B01	205L



CLASSIC 10W MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M006D117	20L
M006D00	25L
M006B01	205L



CLASSIC 20W MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M007D117	20L
M007D00	25L
M007B01	205L



CLASSIC 30 MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M008D117	20L
M008D00	25L
M008B01	205L



CLASSIC 40 MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M009D117	20L
M009D00	25L
M009B01	205L



CLASSIC 50 MINERAL Engine Oil

API SE/CC

	15 x 1L
	4 x 5L
M010D117	20L
M010D00	25L
M010B01	205L



VINTAGE 30 NON DETERGENT MINERAL Engine Oil

API SB

	15 x 1L
	4 x 5L
M123D117	20L
M123D00	25L
M123B01	205L



VINTAGE 40 NON DETERGENT MINERAL Engine Oil

API SB

	15 x 1L
	4 x 5L
M141D117	20L
M141D00	25L
M141B01	205L



VINTAGE 50 NON DETERGENT MINERAL Engine Oil

API SB

	15 x 1L
	4 x 5L
M142D117	20L
M142D00	25L
M142B01	205L



GEAR & TRANSMISSION OILS

Exol offer a comprehensive range of Gear & Transmission oils for the Automotive and Commercial sectors. Contact your Account Manager if you require a brochure, or alternatively visit www.exol-lubricants.com/downloads for an electronic copy.



OPTIMA 4T SS 10W-40 SEMI-SYNTHETIC Engine Oil

JASO MA2, MA, API SL

M441S572	15 x 1L
M441S772	4 x 5L
M441D117	20L
M441D00	25L
M441B01	205L



OPTIMA RACING 2 STROKE FULLY SYNTHETIC Two Stroke Oil

JASO FD, ISO-L-EGD, API TC

M124S523	15 x 1L
M124S704	4 x 5L
M124D117	20L
M124D00	25L
M124B01	205L



OPTIMA SUPER 2 STROKE SEMI SYNTHETIC Two Stroke Oil

JASO FD, ISO-L-EGD, API TC

M222S100	24 x 100ML
	15 x 1L
	4 x 5L
M222D117	20L
M222D00	25L
M222B01	205L



OPTIMA 2 STROKE MINERAL Two Stroke Oil

JASO FB, ISO-L-EGD, API TC

M095S522	15 x 1L
M095S722	4 x 5L
M095D117	20L
M095D00	25L
M095B01	205L



BULK DELIVERY

Exol's fleet of vehicles comprises a mix of dual-purpose vehicles and large tanker trucks to enable us to deliver bulk orders ranging from 500 litres to 32,000 litres on one vehicle.

Ridged Truck dimensions

Length: 36',

Width: 8'6" - requires a minimum of 12' clearance

Height: 12'6"

Tanker Truck dimensions

Length: 68',

Width: 8'6" - requires a minimum of 12' clearance

Height: 12'6"



ULTRAMAX BRAKE FLUID DOT 4 SYNTHETIC

Hydraulic Brake Fluid

US FM VSS 116 DOT 4,
US FM VSS 116 DOT 3,
SAE J1703, J1704,
ISO 4925 (CLASSES 3 & 4)

H053SS436	24 x 250ml
H053SS435	25 x 500ml
H053SS535	15 x 1L
H053S735	4 x 5L
H053D117	20L



ULTRAMAX LHM FLUID PLUS MINERAL

Hydraulic Brake Fluid

ISO 7308, PSA B71 2710,
NEW HOLLAND
NH-610A, FORD M6C59-A

H104S518	15 x 1L
	4 x 5L
H104D117	20L
H104D00	25L
H104B01	205L



ULTRAMAX CHF FULLY SYNTHETIC

Automotive Hydraulic Fluid

AUDI/VOLKSWAGEN G 002 000 A2, TL 52 146.00, BENTLEY RH 5000, BMW/MINI 82 11 1 468 041, 82 11 0 148 132, 83 29 0 429 576, FENDT X 902 011 622, FORD WSS-M2C204-A, MAN M3289, MB 001 989 24 03 10, 001 989 24 03 12, Q 1 32 0001, MB 345.0, PORSCHE 000 043 203 33, SAAB 3032 380, VOLVO 11 61 529, ZF TE-ML 02K
(See Technical Data Sheet for further information)

H201S535	15 x 1L
	4 x 5L
H201D117	20L
H201D00	25L
H201B01	205L



EXCEL DELTA DEGREASER

Solvent Based Cleaner

	15 x 1L
	4 x 5L
D002D117	20L
D002D00	25L
D002B01	205L



EXCEL FLEETWASH

Traffic Film Remover

	15 x 1L
	4 x 5L
D003D117	20L
D003D00	25L
D003B01	205L

TANK MONITORING SYSTEM



Our new Tank Monitoring system allows customers with bulk containers to monitor volume more efficiently.

The system's central, secure databases communicate with remote transmitters using mobile and internet networks. Exol's new system puts customers in complete control while offering a vast range of beneficial features including 24/7 monitoring, increasing traceability and improving stock check.

A high-tech alarm and innovative monitoring equipment is fitted to the tank with the remote monitoring technology informing the customer when the tank needs to be emptied or filled after reaching a set level. Email or text alerts are also available, notifying the customer with consumption.

The sensor is compatible with a range of telematic platforms, enabling you to receive important data from the platform that best suits your requirements. Essential carbon and energy reporting is also provided, and energy reporting is also provided, including Carbon Reduction Credits and DECC calculations, helping you comply with environmental regulations.

The new sensors allow customers to take control of their assets while offering a monitoring solution with complete visibility, highlighting our commitment to providing added value in all areas of business.



OPTICOL ANTIFREEZE RED

Organic Acid
Technology (OAT)

ASTM D3306, ASTM D 4985, SAE J 1034, BS 6580: 2010, AFNOR NF R15-601*, FFV Heft R443, CUNA NC 956-16, UNE 26361-88, JIS K 2234*, NATO S 759 (* with the exception of reserve alkalinity)

D017S535	15 x 1L
D017S704	4 x 5L
D017D117	20L
D017D00	25L
D017B01	205L



OPTICOL ANTIFREEZE RED

50% Organic Acid
Technology (OAT)

ASTM D3306, ASTM D 4985, SAE J 1034, BS 6580: 2010, AFNOR NF R15-601*, FFV Heft R443, CUNA NC 956-16, UNE 26361-88, JIS K 2234*, NATO S 759 (* with the exception of reserve alkalinity)

	15 x 1L
	4 x 5L
D020D117	20L
D020D00	25L
D020B01	205L



OPTICOL ANTIFREEZE BLUE

Inorganic Acid
Technology (IAT)

ASTM D 3306, ASTM D 4985, SAE J 1034, BS 6580: 2010

D001S564	15 x 1L
D001S704	4 x 5L
D001D117	20L
D001D00	25L
D001B01	205L



OPTICOL ANTIFREEZE BLUE

50% Inorganic Acid
Technology (IAT)

ASTM D 3306, ASTM D 4985, SAE J 1034, BS 6580: 2010

	15 x 1L
	4 x 5L
D021D117	20L
D021D00	25L
D021B01	205L



OPTICOL ANTIFREEZE HD (GREEN) OAT + Borate, Silicate, Nitrite (Hybrid)

ASTM D 3306, ASTM D 4985, ASTM D 6210, SAE J 1034, BS 6580 (2010), AFNOR NF R15-601, JIS K2234. MAN 324, Cummins ES14603, Leyland, Fiat / Iveco, BR 637, Perkins, John Deere

(See Technical Data Sheet for further information)

D027S535	15 x 1L
D027S704	4 x 5L
D027D117	20L
D027D00	25L
D027B01	205L



OPTICOL ANTIFREEZE HDX (BLUE/GREEN)

OAT + Borate, Silicate
(Nitrite Free Hybrid)

ASTM D 3306, ASTM D 4985, SAE J 1034, BS 6580, AFNOR NF R15-601, JIS K2234, and the performance requirements of ASTM D 6210

(See Technical Data Sheet for further information)

D031S535	15 x 1L
D031S704	4 x 5L
D031D117	20L
D031D00	25L
D031B01	205L



OPTICOL ANTIFREEZE SOAT (LILAC)

OAT + Silicate (Si-OAT)

ASTM D 3306, ASTM D 4985, SAE J 1034, AFNOR NF R15-601*, CUNA NC 956-16, UNE 26361-88, JIS K 2234*, NATO S 759, BS 6580 (2010), VAG TL 774 G

(* with the exception of reserve alkalinity)

(See Technical Data Sheet for further information)

D032S535	15 x 1L
D032S704	4 x 5L
D032D117	20L
D032D00	25L
D032B01	205L



OPTICOL ANTIFREEZE UNIVERSAL (CLEAR)

OAT (Universal Top Up Coolant)

ASTM D 3306, ASTM D 4985, SAE J 1034, AFNOR NF R15-601*, BS 6580, CUNA NC 956-16, UNE 26361-88, JIS K 2234*, NATO S 759

(* with the exception of reserve alkalinity)

(See Technical Data Sheet for further information)

D033S535	15 x 1L
D033S704	4 x 5L
D033D117	20L
D033D00	25L
D033B01	205L



**LIBRA EP2
MULTI PURPOSE**
Lithium Grease

NLGI 2

Z005K16	CART 400g
Z005K11L	LS CART 400g
	SCREW CART 500g
Z005K15	TIN 500g
Z005K13	3KG
Z005K10	12.5KG
Z005K04	50KG
Z005K01	180KG



COPPER GREASE
Anti-Seize Compound

NLGI 2

	CART 400g
	LS CART 400g
	SCREW CART 500g
Z010K15	TIN 500g
Z010K13	3KG
Z010K10	12.5KG
Z010K04	50KG
	180KG



LITHIUM COMPLEX
Lithium Complex Grease

NLGI 2

Z011K16	CART 400g
Z011K11L	LS CART 400g
	SCREW CART 500g
	TIN 500g
Z011K13	3KG
Z011K10	12.5KG
Z011K04	50KG
Z011K01	180KG



CV JOINT GREASE
Grease for Constant
Velocity Joints

NLGI 2

Z035K16	CART 400g
	LS CART 400g
	SCREW CART 500g
	TIN 500g
Z035K13	3KG
Z035K10	12.5KG
	50KG
	180KG



**BLUE LITHIUM
COMPLEX**
Lithium Complex Grease

NLGI 2

Z074K16	CART 400g
	LS CART 400g
	SCREW CART 500g
	TIN 500g
	3KG
Z074K10	12.5KG
Z074K04	50KG
	180KG

ASK THE EXPERTS

Contact Exol for any issues or technical help.
No matter what the question, our team are here to help.
Use the following communication lines:



+44(0)121 568 6800



hello@exol-lubricants.com



www.exol-lubricants.com



HOW TO FIND THE PERFECT OIL

To ensure you are picking the correct oil for your vehicle, Exol's OIL Check couldn't be easier:

www.exol-lubricants.com/oil-check

Simply enter your car registration

User friendly on-screen instructions

Safe in the knowledge you have the correct information



Simply enter the vehicle's registration number and we'll do the rest. We can then provide you with an overview of the optimum lubricants for your vehicle.



EXOL LUBRICANTS LIMITED

All Saints Road, Wednesbury, West Midlands, WS10 9LL, United Kingdom

T: + (0) 121 5686800

F: + (0) 121 5686720

www.exol-lubricants.com

 **MADE IN ENGLAND**

