



# Taurus Euro FE 5W-30

Fully synthetic, low SAPS, fuel saving, heavy duty engine oil

Product code: M446

## Product Description:

Taurus Euro FE 5W-30 is a state of the art, fully synthetic engine oil designed to offer the user exceptional fuel saving benefits. It achieves this by using a synergistic combination of premium synthetic base stocks, specialised polymers and performance additives blended to an optimised SAE 5W-30 viscosity grade. Taurus Euro FE 5W-30 is compatible with exhaust after-treatment devices such as diesel particulate filters and selective catalytic reduction units.

Static engine tests and field trials have demonstrated that the chemistry employed by Taurus Euro FE 5W-30 is capable of delivering a typical fuel economy improvement of 2%, resulting in potentially huge savings on fuel cost.

## Benefits:

- Exceptional fuel saving benefits
- Compatible with after-treatment devices
- Low oil consumption
- Outstanding anti-wear protection
- Wide range of applications
- Excellent cold starting properties

## Applications:

Taurus Euro FE 5W-30 is ideally suited for use in many of the latest Euro 6 emission engines and is backwards compatible to older models. It is the perfect choice for a typical heavy-duty fleet operator running a range of vehicle types and ages and who wishes to reduce fuel costs.

## Product Specification:

<b>ACEA</b>	E6, E9, E7
<b>API</b>	CJ-4/SN
<b>Daimler Truck</b>	DTFR 15C110 (formerly MB 228.51) DTFR 15C100 (formerly MB 228.31)
<b>MAN</b>	M3677, M3477, M3271-1
<b>Volvo</b>	VDS-4, VDS-3, CNG
<b>Renault Trucks</b>	RXD, RLD-3, RLD-2, RGD
<b>Voith Retarder</b>	Oil Class B

<b>MTU</b>	Type 3.1
<b>Cummins</b>	CES 20081
<b>Caterpillar</b>	ECF-3
<b>Deutz</b>	DQC IV-10 LA
<b>JASO</b>	DH-2
<b>Mack</b>	EO-O PP, EO-N PP, EO-M Plus
<b>Scania</b>	Low Ash



## TECHNICAL DATA SHEET

### Typical Test Data:

Specific Gravity @ 15°C	0.855
Kinematic Viscosity @ 100°C	11.4
Kinematic Viscosity @ 40°C	69.7
Viscosity Index	160
Pour Point (°C)	- 48
Flash Point COC (°C)	226
TBN (mg KOH/g)	10.0
Sulphated Ash (% wt)	0.99