



Autotrans D III

Semi synthetic automatic transmission fluid

Product code: A020

Product Description:

Autotrans D III is a multi-purpose automatic transmission fluid for commercial and passenger car gearboxes meeting a very wide range of specifications. The automatic transmission is one of the most complicated mechanisms in modern automotive engineering and consequently requires complex fluids for efficient operation.

Autotrans D III is manufactured from premium synthetic base stocks and high quality solvent refined base oils with specially selected additives and friction modifiers to produce a lubricant with outstanding durability. It demonstrates excellent frictional stability and offers extended fluid life even when under the most severe conditions.

Benefits:

- Long oil life
- Improves clutch durability
- Can be used as a power steering fluid
- Excellent protection against wear
- Low foaming tendencies
- Compatible with all elastomers and other sealing materials
- High thermal stability

Applications:

Autotrans D III is recommended for automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial machines where the following specifications are required.

Product Specification:

GM	Dexron IIIH, Dexron IIIG Dexron IID, TASA
Ford	Mercon
Allison	C-4, TES-389
Mercedes-Benz	236.10, 236.9, 236.8, 236.7, 236.6, 236.5, 236.1
Caterpillar	TO-2

MAN	339F, 339 V1 & Z1 339 V2 & Z2
Voith	55.6335 (G607)
Volvo	97341, 97340
ZF	TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C



TECHNICAL DATA SHEET

Typical Test Data:

Appearance	Red fluid
Density @ 15°C	0.882
Kinematic Viscosity @ 100°C (cSt)	7.69
Kinematic Viscosity @ 40°C (cSt)	36.4
Viscosity Index	189
Flash Point COC (°C)	205
Pour Point (°C)	-45

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.