



Optifarm UTTO

Universal fluid for tractor transmissions, hydraulics, final drives, and wet brakes

Product Code: A006 (dyed red) or A027 (undyed)

Product Description:

Optifarm UTTO is a modern Universal Tractor Transmission Oil for transmissions, hydraulics, final drives and wet brake systems. The very latest agricultural machinery in the modern intensive farming environment needs the protection of a high quality lubricant. Multi-purpose oils are a good compromise but many manufacturers have realised the benefits of using lubricants specifically designed for a given application.

Optifarm UTTO is blended from carefully selected mineral base oils and the very latest in additive technology to produce a specialised lubricant to meet the latest and most severe transmission requirements. It meets the demands of most agricultural transmission specifications and greatly reduces wet brake noise and chatter. It offers outstanding antiwear performance under the most severe conditions.

Benefits:

- Outstanding anti-wear protection
- Meets the very latest OEM requirements
- Helps reduce wet brake noise and chatter
- Excellent low temperature properties

Application:

Optifarm UTTO is suitable for most modern tractor transmissions, hydraulics, final drives and wet brake systems. Optifarm UTTO is available either undyed or dyed red for easy identification.

Performance Specification:

API	GL-4
John Deere	J20C, J20A
Massey Ferguson	M1145, M1143, M1141, M1135
Case	MAT 3525, MS 1206, MS 1210
New Holland	NH 420A, NH 410B
Volvo	WB101, 97303
Ford	ESN-M2C134-D, ESN-M2C86-B
ZF	TE-ML 03E, 03L, 05F, 06E, 06F, 06K, 06P, 17E, 21E, 21F
Kubota	UDT
Allison	C-4
Caterpillar	TO-2
Valtra	G2-08, G2-B10, G2-A22



TECHNICAL DATA SHEET

Typical Test Data:

Appearance	Clear and Bright
Colour	Red (A006) or Amber (A027)
Specific gravity @ 15.6°C	0.883
Kinematic viscosity @ 100°C (cSt)	9.70
Kinematic viscosity @ 40°C (cSt)	61.9
Viscosity index	141
Flash point COC (°C)	224
Pour point (°C)	-38